

INDUSTRIAL ASPHALT EMULSION **SGDP-500**

DESCRIPTION

INDUSTRIAL ASPHALT EMULSION ADP-205 is a chemical type anionic emulsion of a specially refined high penetration asphalt in water. This emulsion is very stable, and will blend well with many fillers, fibers, and other anionic or nonionic dispersions. It will also readily accept dilution with clean water. **INDUSTRIAL ASPHALT EMULSION SGDP-500**

USES

Used where a 'workhorse' asphalt emulsion is required in formulations for coatings, sealants, and adhesives.

PHYSICAL PROPERTIES

Test	Test Method	Minimum	Maximum
<i>On emulsion:</i>			
pH		11	13
Solids content ,% by mass	ASTM D-244	58	62
Viscosity ,SFS @25°C	ASTM D-244	20	100
Sieve test,%	ASTM D-244		0.1
Residue by distillation,% by mass	ASTM D-244	58	62
Storage Stability, 24hr,% by mass	ASTM D-244		1
<i>On the residue from 260°C distillation:</i>			
Penetration (25°C,100g,5sec), 0.1mm	ASTM D-5	85	200

Colour: Brown(wet); Black (dry)
Specific gravity: 1.0

NaturaSeal Distribution Inc.
960 Edgeley Blvd, Unit 4, Vaughan, ON, L4K 4V4
1-855-797-SEAL, (905) 827-7221 Fax: (905) 563-5582
info@naturaseal.com, www.naturaseal.com

The information contained herein is based on available data and is provided for information only. NATURASEAL. makes no warranties, Representations as to suitability of use, guarantees or conditions, expressed or implied, regarding the accuracy of the data or its use therein. NATURASEAL. will not be liable for any damages arising from the use of the information or product described on this data sheet. PRODUCT DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

LIMITATIONS

Subject to damage if frozen. NOT COMPATIBLE WITH CATIONIC MATERIALS.

Information provided in this bulletin is intended as a guide only; potential users must base judgements on the suitability of this product on their own laboratory and field evaluations.

CLEAN UP

Use water when wet or any suitable safety solvent when dry.

APPLICATION

DampSeal should be applied at a dry film thickness of 15 mils followed by an installation of a protective layer of dimple membrane.

SHELF LIFE

Up to 12 months in sealed containers. Keep containers tightly closed when not in use. KEEP FROM FREEZING.

CAUTIONS

FOR INDUSTRIAL ONLY. Keep out of reach of children. Refer to MSDS for further information.

THIS PRODUCT IS NOT SUBJECT TO THE CONTROLLED PRODUCTS REGULATION

Effective:	12-JAN-15
Replaces:	15-Jun-09

NaturaSeal Distribution Inc.
960 Edgeley Blvd, Unit 4, Vaughan, ON, L4K 4V4
1-855-797-SEAL, (905) 827-7221 Fax: (905) 563-5582
info@naturaseal.com, www.naturaseal.com

The information contained herein is based on available data and is provided for information only. NATURASEAL makes no warranties, Representations as to suitability of use, guarantees or conditions, expressed or implied, regarding the accuracy of the data or its use therein. NATURASEAL will not be liable for any damages arising from the use of the information or product described on this data sheet. PRODUCT DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.